

Model Show: P133-9HSD (P133-9HD: W/O SDI)		Specification	
	Description	13.3" Aluminum Design IPS Full HD 1920×1080 3G -SDI/ 4K HDMI Pro Broadcast Monitor	
	Model	P133-9HSD (P133-9HD: W/O SDI)	
	Screen size	13.3" IPS	
	Display Colors	16.7M	
	Resolution	1920×1080 pixels	
	Dot pitch	0.1533(H)×0.1533(V) mm	
	Aspect Ratio	16:9	
	Brightness	400cd/m ²	
	Contrast	1000:1	
	Backlight	LED	
	Response Time	Tr + Tf=26ms	
	Viewing Angle	85°/85°(L/R) 85°/85°(U/D)	
	Inputs	3G-SDI, HDMI, YPbPr, Video, Audio(L/R), DVI-I, Tally, USB Upgrade	
	Outputs	3G-SDI, HDMI, YPbPr, Video	
	Audio	3.5mm Stereo Headphone, Speaker	
	SDI Support Format	480i/576i	
		720p (60/59.94/50/30/29/25/24/23.98)	
		1080i (60/59.94/50)	
	HDMI Support Format	1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)	
		480i/576i/480p/576p	
		720p (60/59.94/50/30/29/25/24/23.98)	
		1080i (60/59.94/50)	
Power Consumption	≤12W		
Input Voltage	DC9 ~ 24V		
Working Temperature	-10°C~50°C		
Storage Temperature	-20°C~60°C		
Unit Size	315.5L×231H×26.4D mm (W/O Bracket)		
Unit Weight	1.64kg (W/O Bracket)/ 1.96kg (W/Bracket)		
Advanced Features			
*Support 4K HDMI Input and Output			
*Peaking Focus Assist (Red highlight over parts of the monochrome image in focus)			
*Center Marker			
*Screen Marker (80%, 85%, 90%, 93%, 96%, 2.35:1)			
*Image Freeze			
*Image Flip (H, V, H/V)			
*Camera 5D II Mode			
*Check Field (Red, Green, Blue, Mono)			
*Pixel to Pixel (Nonsupport in 4K input)			
*Zoom All (Nonsupport in 4K input)			
*U/D & L/R Zoom (Nonsupport in 4K input)			
*Aspect Ratio (Nonsupport in 4K input)			
*Color Temperature Adjustment			
*Built-in LED tally indicators (Red, Green, Yellow)			
Standard Accessory	Optional Accessory	Packing Details	
1.5A DC Power Adapter	DVI to VGA converter	Box size	37x34.7x10CM
V-Mount Battery Plate	Anton Bauer Battery Plate	Per box G.W.	2.86KG
Mini HDMI Cable	Suitcase	Per Carton	5pcs
Tally Kit		Carton Size	60.5x40.5x39 CM
Sunshade		G.W.	
U bracket			
Operation Manual			